



CONTEC Front Wheel "Xeta + CONTEC Core CL "

29" Front Wheel

RRP 99,95 €

Our Xeta Core 30 29" Boost Front Wheel will win you over with its exceptional durability, whether you're tackling big or small challenges during sporty rides or on your everyday commutes. With a maximum load capacity of up to 150 kg, our Wheel has plenty of reserves for demanding rides, heavier Fahrers, and modern E-MTBs. The Core front wheel hub, featuring a Centerlock brake disc mount and a 15 mm Thru Axle, boasts a proven, robust design for minimal maintenance. The hub is made of aluminum. 32 bent 2 mm stainless steel spokes also ensure a high load capacity. The Xeta Max aluminium rim is tubeless-ready and, with a 30 mm inner rim width, is ideally suited for high-volume tires. All CONTEC wheels are assembled by experienced specialists at our wheel manufacturing facility in Hoya, Lower Saxony (Germany), and perfectly trued using state-of-the-art technology.

Datos maestros

Número de artículo del proveedor:	F=3498164 N=7466211
EAN	4251971143012
UVP	99,95 €
Bidex-Code	204060
DST-Code	2P01
Fedas-Code	160461
SB-Artículo	No
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	1 kg

Datos técnicos

Agujero del radio	easy eyelets
Alojamiento de freno	disc - Center Lock
Altura de la llanta	18.1 mm
Anchura de montaje	110 mm
Artículo	Article
Color del buje	black
Color de llanta	black
Color de radio	black
Color principal	Negro
Diámetro de radio	2,00 mm
ETRTO	30-622
Eje	15mm full-floating axle
Longitud del radio derecho	292 mm
Longitud del radio izquierdo	294 mm
Material de radios	stainless steel
Medida de Ruedas	28 / 29 "
Modelo de cubo	Core

Modelo de llanta	Xeta
Montaje	front wheel
Número de orificios para radios	32 holes
Para rueda	yes
Peso máximo admisible del sistema	150 kg
Sistema de frenado	for disc brake, Center Lock
Sistema tubeless	tubeless ready
Tipo de bicicleta eléctrica	ready
Tipo de llanta	tubeless ready
Tipo de válvula	Sclaverand (SV)
Versión	doublewall
Ámbito de aplicación	MTB