

Rotary 2-post lift "SPO-Serie"

"SPOA3TS-5-EH2", incl. 2nd Operating Unit "CONTROL - SPOA3TC-NC" Load capacity: 3500 kg, total height: 4170 mm, Structure: asymmetrical, Operation: electric

Technical data:

Lifting height: 1957 mm

Lifting time: 30 s

Column spacing: 2544 mm

Drive-through width: 2336 mm

Total width: 3000 mm

Drive power: 4.0 kW

Drive voltage: 400 V / 50 Hz

Total height EH 2: 4170 mm

Cut-off height EH 2: 4026 mm

Support arm length front min. / max.: 857 / 1143 mm

Support arm length hi. min. / max.: 876 / 1474 mm

Turntable height min. / max.: 100 / 160 mm

RRP: 9.768,75 €

Datos maestros

Número de artículo del proveedor:	SPOA3TS-EH2-EV
UVP	9.768,75 €
SB-Artículo	No
Marca/Proveedor	Rotary
Unidad de medida:	PIECE

Datos técnicos

Altura	417.0 cm
Altura de elevación máx.	195.7 cm
Anchura	300.0 cm
Artículo	Article
Características	without base frame
Carga	3500.0 kg
Categoría	2-post lift
Color principal	Plata
Potencia motriz	4.0 kW
Propulsión	electrohydraulic
Tensión de propulsión	400.0 V
Versión	lift

More product images

