

CONTEC Aluminium Rim "Xeta"

27-622, 605 mm ERD (measured incl. spoke holes), 18 mm high, 27 mm inner width, 31 mm outer width, approx. 578 g

Price: 19,99 €

The ideal basis for building a tubeless-ready Wheel for 29" wheels with 32 Spokes. Thanks to the hollow chamber design, the Xeta Max rims made of 6063 aluminum are particularly light and stable. In the finished Wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 27 mm, tires ranging in size from 53 to 69 mm fit on the rim. The single eyeletted nipple holes ensure additional durability of the rim by reducing the friction between the Spoke Nipple and the rim and also prevent the Nipples from working their way into the rim. The Xeta Max rim is only suitable for wheels with disc brakes. You can find suitable tubeless rim tapes in our CONTEC range.

Datos maestros

Número de artículo del proveedor:	30008492
UVP	39,95 €
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Artículo	No
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE

Datos técnicos

Agujero del radio	easy eyelets
Alojamiento de freno	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Altura de la llanta	18 mm
Ancho exterior de la llanta	31 mm
Ancho interior de la llanta	27 mm
Artículo	Article
Cerchio del freno	no
Color principal	Negro
Compatibilidad frenos	disc
ETRTO	27-622
Medida de Ruedas	28 / 29 "
Número de agujeros	32 holes
Para rueda	yes
Peso máximo admisible del sistema	150 kg
Sistema tubeless	tubeless ready
Texto configurador de ruedas	suitable for E-bike
Tipo de válvula	Sclaverand (SV)
Versión	doublewall